

# Fact Sheet



# Digital Detector 1417-I

# 1417-I

This wireless portable flat panel detector is especially designed for EOD application. Due to the excellent image quality the ability to see critical details is raised.

- ✓ Long-time exposure workflow
- ✓ More image details
- ✓ High environmental adaptability
- ✓ High reliability




Figure 1 Very clear image with 100 microns pixel size

**VC**security  
by VisiConsult

<b>Pixel Matrix</b>	3500 x 4300 Pixel
<b>Pixel Pitch</b>	100 µm
<b>Resolution</b>	5 lp/mm
<b>Size</b>	458,4 x 379,2 x 15,68 mm
<b>Imaging Area</b>	43 x 35 cm
<b>Weight</b>	3,8 kg with battery
<b>Dead Space</b>	4,9 mm from bottom, 8 mm from side
<b>Sensor</b>	Amorphous Silicon
<b>Grayscale</b>	16 bits
<b>Ingress Protection</b>	Water resistant and dustproof (IP67)
<b>Environment</b>	- 20°C – +50°C
<b>Drop tested</b>	Up 1 m height
<b>Operating time</b>	Up to 8 hours
<b>Other</b>	Replaceable battery and detachable handle from both sides, magnetic connector, easily replaceable battery with power status LED indication

All images, descriptions and technical specifications are subject to change without prior notice.